



CENTRALINVEST d.o.o



ul. Kralja Milutina 49, 11000 BEOGRAD, SRBIJA tel : + 381 11 3650104; e-mail : office@centralinvest-bg.com

AKCIJA!!!

OKTOBAR 2015.

CREVA ZA ZAVARIVANJE PO NAJPOVOLJNIJIM CENAMA!

Tip creva	dostupna količina	cena bez PDV-a din/m
GAC 6,3x3	1600m	80,00
GOX 8x3	2000m	100,00
GAC 12,5x5	3000m	150,00
GAC 16x5	1000m	250,00

***AKCIJA TRAJE DOK TRAJU ZALIHE**

SEMPERIT

GAC

Welding Hose



Application:

- ☑ A flexible hose for the transport of acetylene.
- ☑ For welding and cutting, for arc welding under protective gas and related processes.
- ☑ Also suitable for hydrogen, coal gas and carbon dioxide, argon, nitrogen for welding and cutting (not suitable for LPG, MPS and CNG).

Standard/approval:

- ☑ ISO 3821:2008 (formerly EN 559:2003).

Notice:

- ☑ Smooth cover available on request.
- ☑ Also available in 40 m lengths.



Temperature range: -30°C / +70°C.

Safety factor: 3 : 1

Tube: EPDM, black, smooth.

Reinforcement: Textile spiral construction.

Cover: EPDM, red, fluted; smooth (from ID12 mm)

Marking: Continuous coloured marking, black: "SEMPERIT S GAC ISO 3821 (EN559) PN 2 MPa (20 bar) DN -30°C quarter/year".

SEMPERIT

GOX

Welding Hose



Application:

- ☑ A flexible hose for transporting oxygen.
- ☑ For welding and cutting, for arc welding using shielding gas and related processes (Not suitable for LPG, MPS and CNG).

Standard/approval:

- ☑ ISO 3821:2008 (formerly EN 559:2003).

Notice:

- ☑ Smooth cover available on request.
- ☑ Also available in 40 m lengths.



Temperature range: -30°C / +70°C.

Safety factor: 3 : 1

Tube: EPDM, black, smooth.

Reinforcement: Textile spiral construction.

Cover: EPDM, blue, fluted; smooth (from ID12 mm).

Marking: Continuous coloured marking, black: "SEMPERIT S GOX ISO 3821 (EN559) PN 2 MPa (20 bar) DN -30°C quarter/year".